

View Online at <https://aerobasegroup.com/nsn/5930-00-552-9166>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Fungus proof and moisture proof

Overall Length:

5.312 inches

Case Material:

Metal

Actuator Style:

Round

Actuator Diameter:

0.500 inches

Housing Height:

2.562 inches

Housing Length:

4.562 inches

Housing Width:

2.625 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

2.875 inches

Maximum Voltage Rating In Volts:

440.0 ac and 120.0 dc

Inclosure Type:

Fully enclosed

Thready Qty Per Inch (tpi):

18

Thread Size:

0.312 inches

Nonpile-up Contact Arrangement:

2 pole, single throw, normally open, momentary action single switch unit

Switch Release Force:

18.0 ounces

Switch Actuating Force:

26.0 ounces

Actuator Movement:

Between 4.0 pretravel degrees and 6.0 overtravel degrees and 26.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 5.000 amperes inductive dc and 7.500 amperes resistive ac and 7.500 amperes inductive ac

Thread Series Designator:

Unc

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0