

View Online at <https://aerobasegroup.com/nsn/5930-00-552-9587>

**Body Style:**

Bushing mount

**Overall Length:**

0.840 inches

**Overall Height:**

2.138 inches

**Overall Width:**

0.719 inches

**Bushing Length:**

0.470 inches

**Body Length:**

0.840 inches

**Body Width:**

0.719 inches

**Actuator Style:**

Round

**Actuator Diameter:**

0.245 inches

**Actuator Height:**

0.690 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained and center position maintained

**Actuator Position-locking Relationship:**

Up position locked in and down position locked in and center position locked in

**Maximum Voltage Rating In Volts:**

250.0 ac and 30.0 dc

**End Application:**

Strategic weapon systems (poseidon & trident)

**Mounting Surface To Terminal End Distance:**

0.928 inches

**Inclosure Type:**

Hermetically sealed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, three positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0