

View Online at <https://aerobasegroup.com/nsn/5930-00-552-9587>

Body Style:

Bushing mount

Overall Length:

0.840 inches

Overall Height:

2.138 inches

Overall Width:

0.719 inches

Bushing Length:

0.470 inches

Body Length:

0.840 inches

Body Width:

0.719 inches

Actuator Style:

Round

Actuator Diameter:

0.245 inches

Actuator Height:

0.690 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked in and down position locked in and center position locked in

Maximum Voltage Rating In Volts:

250.0 ac and 30.0 dc

End Application:

Strategic weapon systems (poseidon & trident)

Mounting Surface To Terminal End Distance:

0.928 inches

Inclosure Type:

Hermetically sealed

Mounting Method:

Threaded bushing

Features Provided:

Actuator seal

Thready Qty Per Inch (tpi):

32

Thread Size:

0.469 inches

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

5.000 amperes resistive dc and 3.000 amperes inductive dc and 5.000 amperes resistive ac

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0