

View Online at <https://aerobasegroup.com/nsn/5930-00-552-9590>

Body Style:

Hole mounted

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.000 inches

Body Length:

1.940 inches

Body Width:

0.670 inches

Body Height:

0.860 inches

Unthreaded Mounting Hole Diameter:

0.140 inches

Actuator Length:

0.917 inches

Actuator Style:

Roller arm

Actuator Free Position Height:

1.140 inches

Actuator Roller Diameter:

0.380 inches

Actuator Roller Width:

0.160 inches

Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary single switch unit

Switch Release Force:

4.0 ounces

Switch Actuating Force:

26.0 ounces

Actuator Movement:

Between 0.065 pretravel inches and 0.010 overtravel inches and 0.020 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

10.000 amperes resistive dc and 10.000 amperes inductive dc and 1.000 amperes resistive ac and 1.000 amperes inductive ac

Terminal Type And Quantity:

3 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0