

View Online at <https://aerobasegroup.com/nsn/5930-00-552-9940>

Hazardous Locations/environmental Protection:

Explosion proof

Shaft Diameter:

0.500 inches single actuator

Shaft Length:

1.156 inches single actuator

Unthreaded Mounting Hole Diameter:

0.213 inches single mounting facility

Individual Section Quantity:

5

Longest Horizontal Distance Between Mounting Centers:

2.298 inches single mounting facility

Longest Vertical Distance Between Mounting Centers:

2.298 inches single mounting facility

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Bracket single mounting facility and unthreaded hole single mounting facility

Features Provided:

Metallic inclosure

Contact Voltage Rating In Volts:

125.0 ac at sea level

Mounting Facility Pattern:

Four position rectangular single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, square single actuator

Square Shaft Size:

0.250 inches single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Adjustable stop single actuator

Contact Load Current Rating:

10.0 amperes resistive load ac at sea level

Special Features:

Shaft modified by welding onto it a collar buord dwg803753 and machining to od 0.500 in. For garlock seal

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0