

View Online at <https://aerobasegroup.com/nsn/5930-00-553-3569>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Dustproof

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.520 inches

Body Length:

1.250 inches

Body Width:

0.500 inches

Body Height:

0.500 inches

Case Material:

Metal

Unthreaded Mounting Hole Diameter:

0.094 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

0.312 inches

Actuator Style:

Rectangular

Actuator Height:

0.093 inches

Maximum Voltage Rating In Volts:

230.0 ac and 250.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Switch Release Force:

3.0 ounces

Switch Actuating Force:

20.0 ounces

Actuator Movement:

Between 0.037 pretravel inches and 0.023 overtravel inches and 0.046 differential inches

Contact Load Current Rating At Maximum Rated Voltage:

100.000 milliamperes resistive dc and 10.000 amperes resistive ac

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0