## NSN 5930-00-553-4435

Sensitive Switch - Page 1 of 2

**Body Style:**Hole mounted



View Online at https://aerobasegroup.com/nsn/5930-00-553-4435

Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.938 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.998 inches and 1.002 inches
Overall Width:
0.688 inches
Body Length:
1.938 inches
Body Width:
0.688 inches
Body Height:
0.953 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
Between 0.139 inches and 0.142 inches
Actuator Style:
Round
Actuator Diameter:
0.156 inches
Actuator Height:
0.546 inches
Actuator Free Position Height:
1.124 inches
Maximum Voltage Rating In Volts:
460.0 ac and 250.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary single switch unit
Switch Release Force:
4.0 ounces
Switch Actuating Force:
Between 7.0 ounces and 9.5 ounces
Actuator Movement:
0.062 overtravel inches

## NSN 5930-00-553-4435

Sensitive Switch - Page 2 of 2



	Contact Load	<b>Current Ra</b>	ating At	Maximum	Rated V	oltage:
--	--------------	-------------------	----------	---------	---------	---------

250.000 milliamperes resistive dc and 15.000 amperes resistive ac

**Terminal Type And Quantity:** 

3 screw

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0