NSN 5930-00-553-5024

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-553-5024

## **Thread Length:**

0.375 inches single mounting facility

## **Overall Length:**

3.710 inches

# **Overall Height:**

1.484 inches

## **Overall Width:**

1.438 inches

### Shaft Diameter:

0.250 inches single actuator

### Shaft Length:

2.250 inches single actuator

## Nonturn Device Radius:

0.438 inches at 9:00 o'clock

## Individual Section Quantity:

2

## Knob Manufacturer Code:

71590

# Knob Manufacturer Part Number:

P-120

# Nonturn Device Type:

Tab at 9: 00 o'clock

# Operating Tempurature Range:

-65.0/+175.0 degrees celsius

# Switch Contact Basic Design:

Nonpile-up symmetrical

### Pole Quantity:

2 each section rear

### Throw Quantity:

6 each section rear

### **Mounting Method:**

Threaded bushing single mounting facility

### **Features Provided:**

Actuator knob

**Thread Size:** 

0.375 inches single mounting facility

### **Contact Voltage Rating In Volts:**

6.0 lowest dc voltage rating at sea level

# Switch Actuator Indexing Position Quantity:

6 single actuator

Shaft Type:

Round single actuator

# NSN 5930-00-553-5024

Rotary Switch - Page 2 of 2



**Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section rear **Switch Actuator Positioning Increment:** 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 5.5 amperes resistive load highest ac voltage rating at sea level Style Designator: Circular wafer, bushing mount **Thread Series Designator:** Unef single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0