## NSN 5930-00-553-5413

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-553-5413

| Overall Length:   |
|---|
| 8.750 inches  |
| Overall Height:   |
| 7.438 inches  |
| Overall Width:  |
| 7.500 inches  |
| Shaft Diameter:   |
| 0.625 inches single actuator  |
| Shaft Length:   |
| 1.250 inches single actuator  |
| Unthreaded Mounting Hole Diameter:  |
| 0.531 inches single mounting facility   |
| Individual Section Quantity:  |
| 4   |
| Knob Manufacturer Code:   |
| 04009   |
| Longest Horizontal Distance Between Mounting Centers:                         |
| 5.625 inches single mounting facility   |
| Longest Vertical Distance Between Mounting Centers:                           |
| 5.625 inches single mounting facility   |
| Switch Contact Basic Design:  |
| Nonpile-up symmetrical  |
| Pole Quantity:  |
| 1 each section front  |
| Throw Quantity:   |
| 4 each section front  |
| Mounting Method:  |
| Bracket single mounting facility and unthreaded hole single mounting facility |
| Features Provided:  |
| Actuator knob   |
| Contact Voltage Rating In Volts:  |
| 500.0 ac at sea level   |
| Switch Actuator Momentary Position:   |
| Clockwise single actuator   |
| Mounting Facility Pattern:  |
| Four position rectangular single mounting facility                            |
| Switch Actuator Indexing Position Quantity:                                   |
| 4 single actuator   |
| Shaft Type:   |
| Round single actuator   |
| Terminal Type:  |
| Tab w/screw   |

## NSN 5930-00-553-5413

Rotary Switch - Page 2 of 2



| Contact Switching Action |
|--------------------------|
|--------------------------|

Breaks before makes each section front

**Switch Actuator Positioning Increment:** 

90.0 degrees single actuator

**Switch Actuator Stop Device Type:** 

Fixed stop single actuator

**Contact Load Current Rating:** 

200.0 amperes resistive load ac at sea level

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0