## NSN 5930-00-553-5520

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-553-5520

Overall Height:
4.844 inches
Overall Width:
2.344 inches
Body Length:
3.562 inches
Body Height:
2.500 inches
Unthreaded Mounting Hole Diameter:
0.250 inches
Longest Horizontal Distance Between Mounting Centers:
4.219 inches
Longest Vertical Distance Between Mounting Centers:
1.875 inches
Pressure Switch Type:
Gage
Mounting Method:
Flange and unthreaded hole
Features Provided:
Electrical access port
Thready Qty Per Inch (tpi):
18 single pressure connection
Contact Action Stimulus:
Increase
Proof Pressure:
40.00 pounds per square inch
Thread Size:
0.250 inches single pressure connection
Mounting Facility Pattern:
Two position diagonal
Nonpile-up Contact Arrangement:
1 pole, double throw, one position momentary
Terminal Type:
Tab w/screw
Contact Load Current Rating:
15.0 amperes resistive load single voltage
Contact Adjustability:
Deactuation point adjustable and actuation point adjustable
Contact Adjustment Range:
+0.00/+40.00 actuation point pounds per square inch and -0.90/+39.60 deactuation point pounds per square inch
Contact Adjustment Type:

Contact Adjustment Type

Internal deactuation point hex nut and internal actuation point hex nut

## NSN 5930-00-553-5520

Pressure Switch - Page 2 of 2



## **Contact Voltage Rating In Volts:**

115.0 ac at sea level single voltage

**Pressure Connector Type:** 

Plain, threaded internal single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

**Thread Series Designator:** 

Npt single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A048b0