## NSN 5930-00-553-5876

Toggle Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-553-5876

| Body Style:   |
|---|
| Bushing mount   |
| Hazardous Locations/environmental Protection:   |
| Watertight  |
| Overall Length:   |
| 1.125 inches  |
| Overall Height:   |
| 2.313 inches  |
| Overall Width:  |
| 0.750 inches  |
| Bushing Length:   |
| 0.500 inches  |
| Body Length:  |
| 1.312 inches  |
| Body Width:   |
| 0.750 inches  |
| Actuator Style:   |
| Round   |
| Actuator Height:  |
| 0.688 inches  |
| Actuator Position-action Relationship:  |
| Up position maintained and down position maintained   |
| Actuator Color:   |
| Natural single actuator   |
| Maximum Voltage Rating In Volts:  |
| 440.0 ac and 30.0 dc  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Method:  |
| Threaded bushing  |
| Features Provided:  |
| Actuator seal   |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Thread Size:  |
| 0.469 inches  |
| Nonpile-up Contact Arrangement:   |
| 2 pole, double throw, both positions maintained single switch unit  |
| Contact Load Current Rating At Maximum Rated Voltage:   |
| 25.000 amperes resistive dc and 20.000 amperes inductive dc and 7.000 amperes lamp dc and 30.000 amperes motor dc and 5.500 |

**Special Features:** 

Has watertight bushing

amperes resistive ac and 4.000 amperes inductive ac and 5.500 amperes motor ac

## **NSN 5930-00-553-5876** Toggle Switch - Page 2 of 2



| inread Series Designator:  |
|----------------------------|
| Uns                        |
| Terminal Type And Quantity |
| 6 tab, solder lug          |
| Shelf Life:                |
| N/a                        |
| Unit Of Measure:           |
|                            |
| Demilitarization:          |
| No                         |

Fiig: A053a0