

View Online at <https://aerobasegroup.com/nsn/5930-00-553-5876>

**Body Style:**

Bushing mount

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

1.125 inches

**Overall Height:**

2.313 inches

**Overall Width:**

0.750 inches

**Bushing Length:**

0.500 inches

**Body Length:**

1.312 inches

**Body Width:**

0.750 inches

**Actuator Style:**

Round

**Actuator Height:**

0.688 inches

**Actuator Position-action Relationship:**

Up position maintained and down position maintained

**Actuator Color:**

Natural single actuator

**Maximum Voltage Rating In Volts:**

440.0 ac and 30.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Threaded bushing

**Features Provided:**

Actuator seal

**Thready Qty Per Inch (tpi):**

32

**Thread Size:**

0.469 inches

**Nonpile-up Contact Arrangement:**

2 pole, double throw, both positions maintained single switch unit

**Contact Load Current Rating At Maximum Rated Voltage:**

25.000 amperes resistive dc and 20.000 amperes inductive dc and 7.000 amperes lamp dc and 30.000 amperes motor dc and 5.500 amperes resistive ac and 4.000 amperes inductive ac and 5.500 amperes motor ac

**Special Features:**

Has watertight bushing

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0