

View Online at <https://aerobasegroup.com/nsn/5930-00-553-6023>

Thread Class:

2b 2nd mounting facility

Overall Length:

3.562 inches

Overall Height:

2.750 inches

Overall Width:

2.750 inches

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

2.000 inches single actuator

Individual Section Quantity:

1

Longest Horizontal Distance Between Mounting Centers:

2.000 inches 2nd mounting facility

Shortest Horizontal Distance Between Mounting Centers:

0.375 inches 2nd mounting facility

Intermediate Horizontal Distance Between Mounting Centers:

1.750 inches 1st mounting facility

Longest Vertical Distance Between Mounting Centers:

2.000 inches 2nd mounting facility

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section rear

Throw Quantity:

24 single section rear

Mounting Method:

Threaded hole 1st mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.164 inches single mounting facility

Contact Voltage Rating In Volts:

300.0 highest ac voltage rating at sea level

Mounting Facility Pattern:

Four position trapezoid 2nd mounting facility

Switch Actuator Indexing Position Quantity:

24 single actuator

Shaft Type:

Round single actuator

Terminal Type:

Turret

Contact Switching Action:

Breaks before makes single section front

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Contact Load Current Rating:

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

Style Designator:

Tap, square frame

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0