

View Online at <https://aerobasegroup.com/nsn/5930-00-553-6023>

**Thread Class:**

2b 2nd mounting facility

**Overall Length:**

3.562 inches

**Overall Height:**

2.750 inches

**Overall Width:**

2.750 inches

**Shaft Diameter:**

0.250 inches single actuator

**Shaft Length:**

2.000 inches single actuator

**Individual Section Quantity:**

1

**Longest Horizontal Distance Between Mounting Centers:**

2.000 inches 2nd mounting facility

**Shortest Horizontal Distance Between Mounting Centers:**

0.375 inches 2nd mounting facility

**Intermediate Horizontal Distance Between Mounting Centers:**

1.750 inches 1st mounting facility

**Longest Vertical Distance Between Mounting Centers:**

2.000 inches 2nd mounting facility

**Switch Contact Basic Design:**

Nonpile-up symmetrical

**Pole Quantity:**

1 single section rear

**Throw Quantity:**

24 single section rear

**Mounting Method:**

Threaded hole 1st mounting facility

**Thready Qty Per Inch (tpi):**

32 single mounting facility

**Thread Size:**

0.164 inches single mounting facility

**Contact Voltage Rating In Volts:**

300.0 highest ac voltage rating at sea level

**Mounting Facility Pattern:**

Four position trapezoid 2nd mounting facility

**Switch Actuator Indexing Position Quantity:**

24 single actuator

**Shaft Type:**

Round single actuator

**Terminal Type:**

Turret

**Contact Switching Action:**

Breaks before makes single section front

**Switch Actuator Positioning Increment:**

15.0 degrees single actuator

**Contact Load Current Rating:**

500.0 milliamperes resistive load dc at sea level and 50.0 milliamperes inductive load dc at sea level

**Style Designator:**

Tap, square frame

**Thread Series Designator:**

Unc single mounting facility

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A052b0