## NSN 5930-00-556-0374

Thermostatic Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-556-0374

Capillary Tube Length:
180.000 inches
Bulb Length:
6.000 inches
Bulb Diameter:
1.125 inches
Longest Horizontal Distance Between Mounting Centers:
2.406 inches
<b>Shortest Horizontal Distance Between Mounting Centers:</b>
1.203 inches
Longest Vertical Distance Between Mounting Centers:
3.281 inches
Tempurature Sensing Element Type:
Capillary tube-bulb
Operating Tempurature Rating:
150.0 degrees fahrenheit
Mounting Method:
Bracket
Features Provided:
Tubing end seal connection
Contact Action Stimulus:
Increase
Mounting Facility Pattern:
Mounting Facility Pattern: Isosceles triangle
Isosceles triangle
Isosceles triangle Nonpile-up Contact Arrangement:
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  8.6 amperes resistive load third voltage
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  8.6 amperes resistive load third voltage  Contact Adjustability:
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  8.6 amperes resistive load third voltage  Contact Adjustability:  Actuation point adjustable
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  8.6 amperes resistive load third voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range:
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  8.6 amperes resistive load third voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point degrees fahrenheit
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  8.6 amperes resistive load third voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point degrees fahrenheit  Contact Adjustment Type:
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  8.6 amperes resistive load third voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point degrees fahrenheit  Contact Adjustment Type:  External actuation point screw
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  8.6 amperes resistive load third voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point degrees fahrenheit  Contact Adjustment Type:  External actuation point screw  Contact Voltage Rating In Volts:
Isosceles triangle  Nonpile-up Contact Arrangement:  1 pole, single throw, normally open, momentary action  Terminal Type:  Tab w/screw  Contact Load Current Rating:  8.6 amperes resistive load third voltage  Contact Adjustability:  Actuation point adjustable  Contact Adjustment Range: +0.00/+60.00 actuation point degrees fahrenheit  Contact Adjustment Type:  External actuation point screw  Contact Voltage Rating In Volts:  440.0 dc at sea level fourth voltage

## NSN 5930-00-556-0374

Thermostatic Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A048b0