## NSN 5930-00-556-0394

Rotary Switch - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/5930-00-556-0394

| Hazardous Locations/environmental Protection:   |
|---|
| Watertight  |
| Overall Length:   |
| 6.562 inches  |
| Overall Height:   |
| 3.500 inches  |
| Overall Width:  |
| 2.812 inches  |
| Shaft Length:   |
| 2.250 inches single actuator  |
| Individual Section Quantity:  |
| 2   |
| Knob Manufacturer Code:   |
| 03497   |
| Switch Contact Basic Design:  |
| Nonpile-up symmetrical  |
| Features Provided:  |
| Actuator knob   |
| Contact Voltage Rating In Volts:  |
| 600.0 dc at sea level   |
| Switch Actuator Indexing Position Quantity:   |
| 3 single actuator   |
| Shaft Type:   |
| Rectangular/square, threaded hole single actuator   |
| Square Shaft Size:  |
| 0.375 inches single actuator  |
| Terminal Type:  |
| Tab w/screw   |
| Contact Switching Action:   |
| Breaks before makes each section front  |
| Switch Actuator Positioning Increment:  |
| 45.0 degrees single actuator  |
| Contact Load Current Rating:  |
| 20.0 amperes resistive load ac at sea level   |
| Special Features:   |
| Knob designated as pistol grip for type sb1 switch, flush mtdw/3 mtg holes 0.250 in. Diameter in 2 rows, 2 holes 2.000 in. C to c in1 row and |
| 1 hole located on centerline 2.188 in. From first line, escutcheon plate to be marked reading from left to right trip, closed, to close       |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del>-</del>  |
| Demilitarization:   |

## **NSN 5930-00-556-0394** Rotary Switch - Page 2 of 2



Fiig:

A052b0