NSN 5930-00-556-0685

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-556-0685

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Submersible
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 0.517 inches and 0.523 inches
Body Length:
1.250 inches
Body Width:
0.500 inches
Body Height:
0.500 inches
Unthreaded Mounting Hole Diameter:
Between 0.101 inches and 0.104 inches
Actuator Style:
Round
Actuator Diameter:
0.250 inches
Actuator Height:
0.094 inches
Actuator Free Position Height:
0.205 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 pole, double throw, both positions maintained single switch unit
Switch Release Force:
5.0 ounces
Switch Actuating Force:
11.0 ounces
Contact Load Current Rating At Maximum Rated Voltage:
10.000 amperes inductive dc and 10.000 amperes resistive ac
Terminal Type And Quantity:
3 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:

--

NSN 5930-00-556-0685

Sensitive Switch - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A053a0