## NSN 5930-00-556-0873

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-556-0873

Body Style:
Hole mounted
Overall Length:
1.940 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.000 inches
Overall Width:
0.690 inches
Body Length:
1.940 inches
Body Width:
0.690 inches
Case Material:
Plastic
Unthreaded Mounting Hole Diameter:
0.139 inches
Actuator Length:
1.950 inches
Actuator Style:
Leaf
Actuator Free Position Height:
0.750 inches
0.750 inches  Maximum Voltage Rating In Volts:
Maximum Voltage Rating In Volts:
Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc
Maximum Voltage Rating In Volts:  125.0 ac and 125.0 dc  Inclosure Type:
Maximum Voltage Rating In Volts: 125.0 ac and 125.0 dc Inclosure Type: Fully enclosed
Maximum Voltage Rating In Volts:  125.0 ac and 125.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:
Maximum Voltage Rating In Volts:  125.0 ac and 125.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Unthreaded hole
Maximum Voltage Rating In Volts:  125.0 ac and 125.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Unthreaded hole  Nonpile-up Contact Arrangement:
Maximum Voltage Rating In Volts:  125.0 ac and 125.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit
Maximum Voltage Rating In Volts:  125.0 ac and 125.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement:  1 pole, double throw, one position momentary single switch unit Switch Release Force:
Maximum Voltage Rating In Volts:  125.0 ac and 125.0 dc  Inclosure Type: Fully enclosed  Mounting Method: Unthreaded hole  Nonpile-up Contact Arrangement:  1 pole, double throw, one position momentary single switch unit  Switch Release Force:  1.0 ounces
Maximum Voltage Rating In Volts:  125.0 ac and 125.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement:  1 pole, double throw, one position momentary single switch unit Switch Release Force:  1.0 ounces Criticality Code Justification:
Maximum Voltage Rating In Volts:  125.0 ac and 125.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement:  1 pole, double throw, one position momentary single switch unit Switch Release Force:  1.0 ounces Criticality Code Justification: Feat
Maximum Voltage Rating In Volts:  125.0 ac and 125.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement:  1 pole, double throw, one position momentary single switch unit Switch Release Force:  1.0 ounces Criticality Code Justification: Feat Switch Actuating Force:
Maximum Voltage Rating In Volts:  125.0 ac and 125.0 dc Inclosure Type: Fully enclosed Mounting Method: Unthreaded hole Nonpile-up Contact Arrangement: 1 pole, double throw, one position momentary single switch unit Switch Release Force: 1.0 ounces Criticality Code Justification: Feat Switch Actuating Force: 12.0 ounces
Maximum Voltage Rating In Volts:  125.0 ac and 125.0 dc  Inclosure Type:  Fully enclosed  Mounting Method:  Unthreaded hole  Nonpile-up Contact Arrangement:  1 pole, double throw, one position momentary single switch unit  Switch Release Force:  1.0 ounces  Criticality Code Justification:  Feat  Switch Actuating Force:  12.0 ounces  Actuator Movement:

**Special Features:** 

Item must comply with requirements of desc production standard no. L01941; for navy nuclear propulsion plant products only

## NSN 5930-00-556-0873

Sensitive Switch - Page 2 of 2



Terminal Type An	d Quantity:
3 screw	

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A053a0