

View Online at <https://aerobasegroup.com/nsn/5930-00-556-2763>

Body Style:

Hole mount

Hazardous Locations/environmental Protection:

Submersible

Overall Length:

2.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 0.997 inches and 1.027 inches

Overall Height:

2.639 inches

Overall Width:

1.520 inches

Body Width:

1.520 inches

Actuator Style:

Round

Actuator Diameter:

0.430 inches

Actuator Height:

Between 1.031 inches and 1.155 inches

Actuator Position-action Relationship:

Up position maintained and down position maintained and center position maintained

Actuator Position-locking Relationship:

Up position locked out and down position no locking action and center position no locking action

Maximum Voltage Rating In Volts:

115.0 ac and 28.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Nonpile-up Contact Arrangement:

2 pole, double throw, three positions maintained single switch unit

Contact Load Current Rating At Maximum Rated Voltage:

40.000 amperes resistive dc and 20.000 amperes inductive dc and 7.000 amperes lamp dc and 20.000 amperes resistive ac and 15.000 amperes inductive ac and 7.000 amperes lamp ac

Test Data Document:

81340-mil-s-3950 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fig:

A053a0