NSN 5930-00-556-2844

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-556-2844

| Body Style: |
|----------------------------------------------------------------------------|
| Hole mounted |
| Overall Length: |
| 1.938 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| Between 0.999 inches and 1.001 inches |
| Overall Height: |
| 1.078 inches |
| Overall Width: |
| 0.688 inches |
| Body Length: |
| 1.938 inches |
| Body Width: |
| 0.688 inches |
| Body Height: |
| 0.812 inches |
| Unthreaded Mounting Hole Diameter: |
| Between 0.139 inches and 0.143 inches |
| Actuator Style: |
| Round |
| Actuator Diameter: |
| 0.234 inches |
| Actuator Free Position Height: |
| 0.828 inches |
| Maximum Voltage Rating In Volts: |
| 480.0 ac and 250.0 dc |
| Inclosure Type: |
| Fully enclosed |
| Mounting Method: |
| Unthreaded hole |
| Nonpile-up Contact Arrangement: |
| 1 pole, single throw, normally closed, momentary action single switch unit |
| Switch Release Force: |
| 4.0 ounces |
| Switch Actuating Force: |
| Between 22.0 ounces and 28.0 ounces |
| Contact Load Current Rating At Maximum Rated Voltage: |
| 250.000 milliamperes resistive dc and 15.000 amperes resistive ac |
| Terminal Type And Quantity: |
| 2 screw |

N/a

Shelf Life:

NSN 5930-00-556-2844 Sensitive Switch - Page 2 of 2



| | | eas | |
|--|--|-----|--|

Demilitarization:

No

Fiig:

A053a0