NSN 5930-00-557-2118

Sensitive Switch - Page 1 of 2

Body Style:



View Online at https://aerobasegroup.com/nsn/5930-00-557-2118

Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Overall Length:
1.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.500 inches
Overall Height:
1.000 inches
Overall Width:
0.688 inches
Body Length:
1.250 inches
Body Width:
0.500 inches
Body Height:
0.875 inches
Case Material:
Metal
Unthreaded Mounting Hole Diameter:
0.114 inches
Actuator Length:
0.250 inches
Actuator Style:
Rectangular
Actuator Height:
0.125 inches
Actuator Width:
0.297 inches
Actuator Free Position Height:
0.505 inches
Maximum Voltage Rating In Volts:
250.0 ac and 30.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
2 two circuit, double break/double make, one position momentary single switch unit
Switch Release Force:
3.0 ounces

NSN 5930-00-557-2118

Sensitive Switch - Page 2 of 2

Fiig: A053a0



Switch Actuating Force:
33.0 ounces
Actuator Movement:
Between 0.060 pretravel inches and 0.025 overtravel inches and 0.028 differential inches
Contact Load Current Rating At Maximum Rated Voltage:
15.000 amperes resistive dc and 10.000 amperes inductive dc and 15.000 amperes resistive ac
Terminal Type And Quantity:
8 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No