## NSN 5930-00-557-2130

Pressure Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-557-2130

**Thread Class:** 

3b single pressure connection

**Inside Diameter:** 

0.438 inches single connection

**Overall Length:** 

3.490 inches

**Body Diameter:** 

1.430 inches

**Body Length:** 

2.170 inches

**Overall Diameter:** 

1.870 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.190 inches and 0.210 inches

**Pressure Switch Type:** 

Gage

**Mounting Facility Circle Radius:** 

1.120 inches

**Operating Tempurature Rating:** 

Between -65.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:** 

Flange and unthreaded hole

**Features Provided:** 

Electrical access port

Thready Qty Per Inch (tpi):

20 single pressure connection

**Contact Action Stimulus:** 

Increase

**Proof Pressure:** 

400.00 pounds per square inch gage

**Thread Size:** 

0.4375 inches single pressure connection

**Mounting Facility Pattern:** 

Four position circular

**Nonpile-up Contact Arrangement:** 

1 pole, double throw, one position momentary

**Terminal Type:** 

Connector, receptacle

**Contact Load Current Rating:** 

2.5 amperes resistive load single voltage

**Contact Adjustability:** 

Deactuation point not adjustable and actuation point not adjustable

## NSN 5930-00-557-2130

Pressure Switch - Page 2 of 2



Contact	Stimulus	Katır	ıg:
25.00 dea	actuation	point	po

25.00 deactuation point pounds per square inch gage

**Contact Voltage Rating In Volts:** 

28.0 dc at sea level single voltage

**Pressure Connector Type:** 

Plain, threaded internal single connection

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

**Thread Series Designator:** 

Unf single pressure connection

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A048b0