

View Online at <https://aerobasegroup.com/nsn/5930-00-557-2500>

Overall Length:

4.938 inches

Overall Height:

2.875 inches

Overall Width:

3.562 inches

Body Length:

4.875 inches

Body Width:

2.750 inches

Body Height:

2.688 inches

Unthreaded Mounting Hole Diameter:

0.281 inches

Capillary Tube Length:

120.000 inches

Bulb Length:

3.000 inches

Bulb Diameter:

0.375 inches

Longest Horizontal Distance Between Mounting Centers:

1.750 inches

Intermediate Horizontal Distance Between Mounting Centers:

0.656 inches

Longest Vertical Distance Between Mounting Centers:

3.281 inches

Temperature Sensing Element Type:

Capillary tube-bulb

Operating Temperature Rating:

Between -100.0 degrees fahrenheit and 280.0 degrees fahrenheit

Mounting Method:

Bracket and unthreaded hole

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Obtuse triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

8.6 amperes resistive load second voltage

Contact Adjustability:

Deactuation point adjustable and actuation point adjustable

Contact Adjustment Range:

+150.00/+225.00 actuation point degrees fahrenheit and +150.00/+225.00 deactuation point degrees fahrenheit

Contact Adjustment Type:

External deactuation point screw and external actuation point screw

Contact Voltage Rating In Volts:

550.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular w/bracket

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0