# NSN 5930-00-557-6184

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-557-6184

## **Thread Class:**

2b single mounting facility

## **Overall Length:**

3.781 inches

## **Overall Height:**

2.765 inches

## **Overall Width:**

2.765 inches

#### First Flat Length:

0.438 inches single actuator

#### Flat Height:

0.216 inches single actuator

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.812 inches single actuator

# Individual Section Quantity:

2

## Longest Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

## Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

4 each section rear

#### Throw Quantity:

4 each section rear

## **Mounting Method:**

Threaded hole single mounting facility

## Thready Qty Per Inch (tpi):

32 single mounting facility

## Thread Size:

0.164 inches single mounting facility

## **Contact Voltage Rating In Volts:**

115.0 ac at sea level

## **Mounting Facility Pattern:**

Two position in-line single mounting facility

## Switch Actuator Indexing Position Quantity:

4 single actuator

## Shaft Type:

Round, flatted single actuator

## **Terminal Type:**

Tab, solder lug

# NSN 5930-00-557-6184

Rotary Switch - Page 2 of 2



**Contact Switching Action:** Breaks before makes each section rear Switch Actuator Positioning Increment: 30.0 degrees single actuator Switch Actuator Stop Device Type: Fixed stop single actuator **Contact Load Current Rating:** 3.0 amperes resistive load ac at sea level **Precious Material And Location:** Contacts silver **Precious Material:** Silver Style Designator: Tap, square frame **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A052b0