## NSN 5930-00-557-6186

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-557-6186

**Thread Class:** 

2a single mounting facility

Thread Length:

0.469 inches single mounting facility

**Overall Length:** 

2.312 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.192 inches single actuator

**Shaft Diameter:** 

0.249 inches single actuator

**Shaft Length:** 

1.500 inches single actuator

**Overall Diameter:** 

2.188 inches

**Individual Section Quantity:** 

1

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

1 single section front

**Throw Quantity:** 

2 single section front

**Mounting Method:** 

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

**Thread Size:** 

0.469 inches single mounting facility

**Contact Voltage Rating In Volts:** 

24.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

2 single actuator

**Shaft Type:** 

Round, flatted single actuator

**Terminal Type:** 

Tab, solder lug

**Contact Switching Action:** 

Breaks before makes single section front

**Switch Actuator Positioning Increment:** 

45.0 degrees single actuator

## NSN 5930-00-557-6186

Rotary Switch - Page 2 of 2



Contact Load	Current	Rating:
--------------	---------	---------

3.0 amperes resistive load ac at sea level

**Style Designator:** 

Tap, circular, bushing mount

**Thread Series Designator:** 

Uns single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A052b0