

View Online at <https://aerobasegroup.com/nsn/5930-00-557-6187>

Thread Class:

2a single mounting facility

Thread Length:

0.469 inches single mounting facility

Overall Length:

2.688 inches

First Flat Length:

0.500 inches single actuator

Flat Height:

0.182 inches single actuator and 0.192 inches single actuator

Shaft Diameter:

0.245 inches single actuator and 0.249 inches single actuator

Shaft Length:

1.000 inches single actuator

Overall Diameter:

2.188 inches

Individual Section Quantity:

2

Nonturn Device Type:

Slotted bushing at 6: 00 o'clock

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 single section front

Throw Quantity:

3 single section front

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

24.0 dc at sea level

Shaft Flat/slot Angular Location:

135.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Breaks before makes each section front

Switch Actuator Positioning Increment:

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

8.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0