NSN 5930-00-557-7843

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-557-7843

| Body Style: | |
|---|--|
| Hole mounted | |
| Hazardous Locations/environmental Protection: | |
| Watertight | |
| Overall Length: | |
| 3.250 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Length: | |
| 2.375 inches | |
| Overall Height: | |
| 11.156 inches | |
| Overall Width: | |
| 3.188 inches | |
| Body Length: | |
| 3.250 inches | |
| Body Width: | |
| 3.188 inches | |
| Body Height: | |
| 9.250 inches | |
| Case Material: | |
| Metal | |
| Unthreaded Mounting Hole Diameter: | |
| 0.406 inches | |
| Center To Center Distance Between Mounting Facilities Parallel To Height: | |
| 8.375 inches | |
| Actuator Style: | |
| Roller plunger | |
| Actuator Free Position Height: | |
| 1.563 inches | |
| Actuator Roller Diameter: | |
| 0.719 inches | |
| Actuator Roller Width: | |
| 0.250 inches | |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Method: | |
| Unthreaded hole | |
| Nonpile-up Contact Arrangement: | |
| 6 pole, double throw, one position momentary single switch unit | |
| Switch Release Force: | |
| 80.0 ounces | |
| Switch Actuating Force: | |

64.0 ounces

NSN 5930-00-557-7843

Sensitive Switch - Page 2 of 2



| Actuator | Movement: |
|----------|-----------|
|----------|-----------|

10.000 pretravel degrees and 0.040 overtravel degrees and 0.020 differential degrees

Terminal Type And Quantity:

18 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0