

View Online at <https://aerobasegroup.com/nsn/5930-00-558-8607>

Body Style:

Hole mounted

Hazardous Locations/environmental Protection:

Industrial use

Actuator Length:

1.750 inches

Actuator Style:

Roller arm

Actuator Roller Diameter:

0.750 inches

Actuator Roller Width:

0.250 inches

Housing Height:

2.016 inches

Housing Length:

4.938 inches

Housing Width:

2.250 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Length:

4.219 inches

Center To Center Distance Between Housing Mounting Facilities Parallel To Width:

1.813 inches

Maximum Voltage Rating In Volts:

220.0 ac and 220.0 dc

Inclosure Type:

Fully enclosed

Mounting Method:

Unthreaded hole

Features Provided:

Actuator seal

Nonpile-up Contact Arrangement:

1 two circuit, double break/double make, one position momentary single switch unit

Actuator Movement:

11.0 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

1.000 amperes resistive dc and 3.000 amperes resistive ac

Special Features:

Ccw actuation

Terminal Type And Quantity:

4 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A053a0