# NSN 5930-00-560-2624

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-560-2624

#### **Thread Class:**

2a single mounting facility

#### Thread Length:

0.375 inches single mounting facility

# **Overall Length:**

3.469 inches

#### **Overall Height:**

1.500 inches

#### **Overall Width:**

1.359 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.500 inches single actuator

#### **Nonturn Device Radius:**

# 0.375 inches at 9:00 o'clock

#### Individual Section Quantity:

6

#### Nonturn Device Type:

Tab at 9: 00 o'clock

## Switch Contact Basic Design:

Nonpile-up symmetrical

## Pole Quantity:

1 each section rear

#### **Throw Quantity:**

10 each section rear

#### **Mounting Method:**

Threaded bushing single mounting facility

#### **Thread Size:**

0.375 inches single mounting facility

#### Contact Voltage Rating In Volts:

28.0 dc at sea level

#### Switch Actuator Indexing Position Quantity:

10 single actuator

# Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

#### **Contact Switching Action:**

Breaks before makes each section rear

# Switch Actuator Positioning Increment:

30.0 degrees single actuator

# NSN 5930-00-560-2624

Rotary Switch - Page 2 of 2



Switch Actuator Stop Device Type: Fixed stop single actuator

# **Contact Load Current Rating:**

1.0 amperes resistive load ac at sea level

# **Precious Material And Location:**

Contact and rotor blades silver

**Precious Material:** 

Silver

## Style Designator:

Circular wafer, bushing mount

# **Thread Series Designator:**

Unef single mounting facility

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

# Fiig:

A052b0