# NSN 5930-00-562-2053

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-562-2053

#### **Thread Class:**

2b single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

## **Overall Length:**

4.562 inches

#### **Overall Height:**

2.750 inches

#### **Overall Width:**

3.375 inches

#### Shaft Diameter:

0.250 inches single actuator

#### Shaft Length:

0.812 inches single actuator

#### Individual Section Quantity:

8

### Longest Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

2 each section in-line

#### **Throw Quantity:**

3 each section in-line

**Mounting Method:** 

Base single mounting facility and threaded hole single mounting facility

#### **Features Provided:**

Variable resistor and metallic inclosure

#### Thready Qty Per Inch (tpi):

32 single mounting facility

#### **Thread Size:**

0.164 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

115.0 ac at sea level

#### Mounting Facility Pattern:

Two position in-line single mounting facility

## Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round single actuator

#### **Terminal Type:**

Tab, solder lug

# NSN 5930-00-562-2053

Rotary Switch - Page 2 of 2



**Contact Switching Action:** Breaks before makes each section in-line **Switch Actuator Positioning Increment:** 15.0 degrees single actuator **Contact Load Current Rating:** 5.0 amperes resistive load ac at sea level **Precious Material And Location:** Contact surfaces silver **Precious Material:** Silver Style Designator: Tap, circuit selector **Thread Series Designator:** Unc single mounting facility Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A052b0