

View Online at <https://aerobasegroup.com/nsn/5930-00-562-8014>

Thread Class:

2a single mounting facility

Overall Length:

Between 3.812 inches and 3.876 inches

Overall Height:

1.562 inches

Overall Width:

1.938 inches

First Flat Length:

0.422 inches single actuator and 0.454 inches single actuator

Flat Height:

0.188 inches single actuator and 0.204 inches single actuator

Shaft Diameter:

0.250 inches single actuator

Shaft Length:

0.438 inches single actuator

Nonturn Device Radius:

0.375 inches at 10: 30 o'clock

Individual Section Quantity:

4

Nonturn Device Type:

Tab at 10: 30 o'clock

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded bushing single mounting facility

Thread Size:

0.375 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 highest ac voltage rating at sea level

Shaft Flat/slot Angular Location:

0.0 degrees from nonturn device single actuator

Switch Actuator Indexing Position Quantity:

5 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Tab, solder lug

Contact Switching Action:

Makes before breaks each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0