## NSN 5930-00-563-2517

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-563-2517

g
Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Industrial use
Actuator Length:
1.750 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.750 inches
Actuator Roller Width:
0.250 inches
Housing Height:
2.016 inches
Housing Length:
4.938 inches
Housing Width:
2.250 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
4.219 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Width:
1.813 inches
Maximum Voltage Rating In Volts:
220.0 ac and 220.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Features Provided:
Actuator seal
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:
150.0 inch-ounces
Actuator Movement:
11.0 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
1.000 amperes resistive dc and 3.000 amperes resistive ac
Special Features:
Cw actuation

4 screw

**Terminal Type And Quantity:** 

## NSN 5930-00-563-2517

Sensitive Switch - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A053a0