

View Online at <https://aerobasegroup.com/nsn/5930-00-566-5236>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Watertight

**Overall Length:**

3.000 inches

**Overall Width:**

1.032 inches

**Actuator Length:**

3.250 inches

**Actuator Style:**

Roller arm

**Actuator Roller Diameter:**

0.500 inches

**Actuator Roller Width:**

0.130 inches

**Housing Height:**

1.125 inches

**Housing Length:**

2.500 inches

**Housing Width:**

1.032 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

1.563 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

1.875 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Unthreaded hole

**Nonpile-up Contact Arrangement:**

1 two circuit, double break/double make, one position momentary single switch unit

**Switch Actuating Force:**

24.0 ounces

**Actuator Movement:**

Between 4.0 pretravel degrees and 10.0 overtravel degrees and 1.5 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes inductive ac

**Terminal Type And Quantity:**

1 connector, receptacle

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A053a0