NSN 5930-00-566-5236

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-566-5236

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Watertight
Overall Length:
3.000 inches
Overall Width:
1.032 inches
Actuator Length:
3.250 inches
Actuator Style:
Roller arm
Actuator Roller Diameter:
0.500 inches
Actuator Roller Width:
0.130 inches
Housing Height:
1.125 inches
Housing Length:
2.500 inches
Housing Width:
1.032 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
1.563 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.875 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Mounting Method:
Unthreaded hole
Nonpile-up Contact Arrangement:
1 two circuit, double break/double make, one position momentary single switch unit
Switch Actuating Force:

24.0 ounces

Actuator Movement:

Between 4.0 pretravel degrees and 10.0 overtravel degrees and 1.5 differential degrees

Contact Load Current Rating At Maximum Rated Voltage:

15.000 amperes resistive dc and 10.000 amperes inductive dc and 10.000 amperes inductive ac

Terminal Type And Quantity:

1 connector, receptacle

NSN 5930-00-566-5236

Sensitive Switch - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A053a0