

View Online at <https://aerobasegroup.com/nsn/5930-00-566-6859>

Thread Class:

2a single mounting facility

Thread Length:

0.470 inches single mounting facility

Hazardous Locations/environmental Protection:

Shock resistant

Overall Length:

3.150 inches

First Flat Length:

0.690 inches single actuator

Flat Height:

0.182 inches single actuator and 0.192 inches single actuator

Shaft Diameter:

0.248 inches single actuator and 0.252 inches single actuator

Shaft Length:

0.750 inches single actuator

Overall Diameter:

2.130 inches

Individual Section Quantity:

2

Nonturn Device Type:

Slotted bushing at 6: 00 o'clock

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Switch Contact Basic Design:

Nonpile-up symmetrical

Pole Quantity:

1 each section periphery

Throw Quantity:

3 each section periphery

Mounting Method:

Threaded bushing single mounting facility

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.469 inches single mounting facility

Contact Voltage Rating In Volts:

115.0 ac at sea level 28.0 dc at sea level

Switch Actuator Indexing Position Quantity:

3 single actuator

Shaft Type:

Round, flatted single actuator

Terminal Type:

Screw

Contact Switching Action:

Breaks before makes each section periphery

Switch Actuator Positioning Increment:

90.0 degrees single actuator

Contact Load Current Rating:

15.0 amperes resistive load ac at sea level 10.0 amperes inductive load dc at sea level and 15.0 amperes resistive load dc at sea level

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Uns single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A052b0