View Online at https://aerobasegroup.com/nsn/5930-00-566-7787

Overall Length:

84.0 millimeters

Overall Height:

104.0 millimeters

Overall Width:

44.0 millimeters

Body Height:

61.0 millimeters

Unthreaded Mounting Hole Diameter:

5.0 millimeters

Longest Horizontal Distance Between Mounting Centers:

56.0 millimeters

Intermediate Horizontal Distance Between Mounting Centers:

38.4 millimeters

Longest Vertical Distance Between Mounting Centers:

38.4 millimeters

Pressure Switch Type:

Absolute

Operating Tempurature Rating:

Between -40.0 degrees celsius and 65.0 degrees celsius

Mounting Method:

Unthreaded hole

Features Provided:

Electrical access port

Contact Action Stimulus:

Increase

Mounting Facility Pattern:

Obtuse triangle

Nonpile-up Contact Arrangement:

1 pole, double throw, one position momentary

Terminal Type:

Screw

Contact Load Current Rating:

55.0 milliamperes resistive load second voltage

Contact Adjustability:

Actuation point adjustable

Contact Adjustment Range:

+145.10/+464.32 actuation point pounds per square inch

Contact Adjustment Type:

External actuation point screw

Contact Voltage Rating In Volts:

380.0 ac at sea level first voltage

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0