NSN 5930-00-568-3753

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-568-3753

Hazardous Locations/environmental Protection:				
Explosion proof				
Overall Length:				
4.750 inches				
Overall Height:				
2.906 inches				
Overall Width:				
2.813 inches				
Unthreaded Mounting Hole Diameter:				
0.221 inches single mounting facility				
Individual Section Quantity:				
1				
Knob Manufacturer Code:				
82121				
Knob Manufacturer Part Number:				
G				
Longest Horizontal Distance Between Mounting Centers:				
2.000 inches single mounting facility				
Shortest Horizontal Distance Between Mounting Centers:				
1.000 inches single mounting facility				
Longest Vertical Distance Between Mounting Centers:				
2.188 inches single mounting facility				
Switch Contact Basic Design:				
Nonpile-up symmetrical				
Pole Quantity:				
1 single section front				
Throw Quantity:				
7 single section front				
Mounting Method:				
Bracket single mounting facility				
Features Provided:				
Actuator knob				
Contact Voltage Rating In Volts:				
500.0 highest ac voltage rating at sea level				
Mounting Facility Pattern:				
Isosceles triangle single mounting facility				
Switch Actuator Indexing Position Quantity:				
7 single actuator				
Terminal Type:				
Screw				
Contact Switching Action:				

Breaks before makes single section front

NSN 5930-00-568-3753

Rotary Switch - Page 2 of 2



Switch Actuator Positioning Increment:	Switch	Actuator	Positioning	Increment:
--	--------	----------	--------------------	------------

45.0 degrees single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load highest ac voltage rating at sea level

Style Designator:

Tap, circuit selector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A052b0