

View Online at <https://aerobasegroup.com/nsn/5930-00-568-9824>

Thread Class:

2a single mounting facility

Thread Length:

0.219 inches single mounting facility

Hazardous Locations/environmental Protection:

Moisture resistant

Overall Length:

4.000 inches

First Flat Length:

0.250 inches single actuator

Flat Height:

0.219 inches single actuator

Shaft Diameter:

0.245 inches single actuator and 0.255 inches single actuator

Shaft Length:

0.375 inches single actuator

Overall Diameter:

1.875 inches

Individual Section Quantity:

2

Longest Horizontal Distance Between Mounting Centers:

1.375 inches single mounting facility

Operating Temperature Range:

-65.0/+150.0 degrees fahrenheit

Switch Contact Basic Design:

Nonpile-up nonsymmetrical

Mounting Method:

Threaded stud single mounting facility

Features Provided:

Metallic inclosure

Thready Qty Per Inch (tpi):

32 single mounting facility

Thread Size:

0.138 inches single mounting facility

Contact Voltage Rating In Volts:

28.0 dc at sea level

Mounting Facility Pattern:

Two position in-line single mounting facility

Switch Actuator Indexing Position Quantity:

8 single actuator

Shaft Type:

Round, slotted, flatted single actuator

Terminal Type:

Wire lead

Contact Switching Action:

Makes before breaks each section front

Switch Actuator Positioning Increment:

15.0 degrees single actuator

Detent Rotational Torque Range:

+16.000/+50.000 inch-ounces single actuator

Switch Actuator Stop Device Type:

Fixed stop single actuator

Contact Load Current Rating:

5.0 amperes resistive load ac at sea level

Precious Material And Location:

Contacts gold

Precious Material:

Gold

Style Designator:

Tap, circular, bushing mount

Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A052b0