## NSN 5930-00-569-4736

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-569-4736 **Thread Class:** 2a **Body Style: Bushing mounted Hazardous Locations/environmental Protection:** Dustproof and moisture resistant **Body Diameter:** 0.562 inches **Bushing Length:** 0.406 inches **Body Length:** 0.355 inches **Case Material:** Metal **Actuator Diameter:** 0.562 inches **Actuator Height:** 0.281 inches **Maximum Voltage Rating In Volts:** 115.0 ac and 28.0 dc Inclosure Type: Fully enclosed **Mounting Method:** Threaded bushing Thready Qty Per Inch (tpi): 27 **Thread Size:** 0.625 inches **Nonpile-up Contact Arrangement:** 2 two circuit, double break/double make, one position momentary single switch unit **Contact Load Current Rating At Maximum Rated Voltage:** 17.000 amperes resistive dc and 15.000 amperes resistive ac **Thread Series Designator:** Uns **Terminal Type And Quantity:** 4 tab, solder lug Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5930-00-569-4736

Push Switch - Page 2 of 2



Fiig:

A053a0