## NSN 5930-00-569-9523

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-569-9523

**Thread Class:** 

2a single mounting facility

Thread Length:

0.375 inches single mounting facility

**Overall Length:** 

3.000 inches

**Overall Height:** 

1.500 inches

**Overall Width:** 

1.438 inches

**Shaft Diameter:** 

0.250 inches single actuator

**Shaft Length:** 

1.438 inches single actuator

**Nonturn Device Radius:** 

0.438 inches at 12: 00 o'clock

**Individual Section Quantity:** 

•

**Knob Manufacturer Code:** 

71590

**Knob Manufacturer Part Number:** 

P120

**Nonturn Device Type:** 

Tab at 12: 00 o'clock

**Operating Tempurature Range:** 

-65.0/+175.0 degrees celsius

**Switch Contact Basic Design:** 

Nonpile-up symmetrical

**Pole Quantity:** 

2 single section rear

**Throw Quantity:** 

5 single section front

**Mounting Method:** 

Threaded bushing single mounting facility

**Thread Size:** 

0.375 inches single mounting facility

**Contact Voltage Rating In Volts:** 

12.0 dc at sea level

**Switch Actuator Indexing Position Quantity:** 

5 single actuator

**Shaft Type:** 

Round single actuator

## **NSN 5930-00-569-9523** Rotary Switch - Page 2 of 2



Terminal Type:
Tab, solder lug
Contact Switching Action:
Breaks before makes single section rear
<b>Switch Actuator Positioning Increment</b>
30.0 degrees single actuator
Contact Load Current Rating:
3.0 amperes resistive load dc at sea level
Style Designator:
Circular wafer, bushing mount
Thread Series Designator:
Unef single mounting facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A052b0