# NSN 5930-00-571-6077

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-571-6077

#### **Thread Class:**

2b single mounting facility

## Hazardous Locations/environmental Protection:

Dustproof

# **Overall Length:**

6.720 inches

#### Shaft Length:

2.716 inches single actuator

## **Overall Diameter:**

3.750 inches

## Individual Section Quantity:

7

## Knob Manufacturer Code:

82121

#### Longest Horizontal Distance Between Mounting Centers:

2.297 inches single mounting facility

## Longest Vertical Distance Between Mounting Centers:

2.297 inches single mounting facility

#### Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

2 each section rear

#### Throw Quantity:

2 each section rear

#### **Mounting Method:**

Threaded hole single mounting facility

#### Features Provided:

Actuator knob

#### Thready Qty Per Inch (tpi):

24 single mounting facility

#### Thread Size:

0.190 inches single mounting facility

# Contact Voltage Rating In Volts:

125.0 dc at sea level

# Mounting Facility Pattern:

Four position rectangular single mounting facility

# Switch Actuator Indexing Position Quantity:

2 single actuator

# Shaft Type:

Rectangular/square, threaded hole single actuator

# Square Shaft Size:

0.250 inches single actuator

# NSN 5930-00-571-6077

Rotary Switch - Page 2 of 2



**Terminal Type:** 

Tab w/screw

**Contact Switching Action:** 

Breaks before makes each section rear

Switch Actuator Positioning Increment:

30.0 degrees single actuator

# **Contact Load Current Rating:**

5.0 amperes resistive load dc at sea level

## Style Designator:

Tap, circular, bushing mount

#### **Thread Series Designator:**

Unc single mounting facility

Shelf Life:

N/a

#### Unit Of Measure:

---

## Demilitarization:

No

### Fiig:

A052b0