NSN 5930-00-572-0337

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-572-0337

Thread Class: 2a single mounting facility Thread Length: 0.250 inches single mounting facility **Overall Length:** 1.938 inches **Overall Height:** 1.312 inches **Overall Width:** 1.250 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 0.750 inches single actuator **Nonturn Device Radius:** 0.531 inches at 3: 00 o'clock **Individual Section Quantity:** 2 **Nonturn Device Type:** Tab at 3: 00 o'clock **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 1 each section rear **Throw Quantity:** 4 2nd section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 12 single actuator **Shaft Type:** Round single actuator **Terminal Type:** Tab, solder lug **Contact Switching Action:** Breaks before makes each section front **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

NSN 5930-00-572-0337

Rotary Switch - Page 2 of 2



Contact Load Current Rating:

1.0 amperes resistive load ac at sea level

Precious Material And Location:

Clips silver and rotor blade silver

Precious Material:

Silver

Style Designator:

Circular wafer, bushing mount

Thread Series Designator:

Unef single mounting facility

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

No

Fiig:

A052b0