

View Online at <https://aerobasegroup.com/nsn/5930-00-572-4763>

Hazardous Locations/environmental Protection:

Humidity resistant

Overall Length:

1.938 inches

Outside Diameter:

0.125 inches single connection

Overall Height:

3.281 inches

Overall Width:

0.875 inches

Pressure Switch Type:

Gage

Operating Temperature Rating:

Between -67.0 degrees fahrenheit and 160.0 degrees fahrenheit

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Thread Size:

0.125 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, single throw, normally closed, momentary action

Terminal Type:

Tab, solder lug

Contact Load Current Rating:

1.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point adjustable, preset and deactuation point adjustable, preset

Contact Adjustment Range:

+0.00/+60.00 actuation point pounds per square inch and +0.00/+60.00 deactuation point pounds per square inch

Contact Adjustment Type:

External actuation point shaft and external deactuation point shaft

Contact Stimulus Rating:

16.00 actuation point pounds per square inch and 10.50 deactuation point pounds per square inch

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Media For Which Designed:

Gas or liquid

Style Designator:

Rectangular

Thread Series Designator:

Npt single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0