

View Online at <https://aerobasegroup.com/nsn/5930-00-572-4763>

**Hazardous Locations/environmental Protection:**

Humidity resistant

**Overall Length:**

1.938 inches

**Outside Diameter:**

0.125 inches single connection

**Overall Height:**

3.281 inches

**Overall Width:**

0.875 inches

**Pressure Switch Type:**

Gage

**Operating Temperature Rating:**

Between -67.0 degrees fahrenheit and 160.0 degrees fahrenheit

**Mounting Method:**

Input port

**Contact Action Stimulus:**

Increase

**Thread Size:**

0.125 inches single pressure connection

**Nonpile-up Contact Arrangement:**

1 pole, single throw, normally closed, momentary action

**Terminal Type:**

Tab, solder lug

**Contact Load Current Rating:**

1.0 amperes resistive load single voltage

**Contact Adjustability:**

Actuation point adjustable, preset and deactuation point adjustable, preset

**Contact Adjustment Range:**

+0.00/+60.00 actuation point pounds per square inch and +0.00/+60.00 deactuation point pounds per square inch

**Contact Adjustment Type:**

External actuation point shaft and external deactuation point shaft

**Contact Stimulus Rating:**

16.00 actuation point pounds per square inch and 10.50 deactuation point pounds per square inch

**Contact Voltage Rating In Volts:**

28.0 dc at sea level single voltage

**Pressure Connector Type:**

Flared, threaded external single connection

**Media For Which Designed:**

Gas or liquid

**Style Designator:**

Rectangular

**Thread Series Designator:**

Npt single pressure connection

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A048b0