NSN 5930-00-574-2975

Sensitive Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-574-2975

Body Style:
Hole mounted
Hazardous Locations/environmental Protection:
Dustproof
Actuator Style:
Adjustable arm
Actuator Height:
0.937 inches
Actuator Width:
0.437 inches
Housing Height:
1.250 inches
Housing Length:
2.799 inches
Housing Width:
1.218 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Height:
2.588 inches
Center To Center Distance Between Housing Mounting Facilities Parallel To Length:
1.875 inches
Maximum Voltage Rating In Volts:
250.0 ac and 28.0 dc
Inclosure Type:
Fully enclosed
Nonpile-up Contact Arrangement:
2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit
Switch Release Force:
80.0 ounces
Switch Actuating Force:
144.0 ounces
Actuator Movement:
Between 4.0 pretravel degrees and 8.0 overtravel degrees and 1.5 differential degrees
Contact Load Current Rating At Maximum Rated Voltage:
5.000 amperes resistive dc and 5.000 amperes inductive dc and 10.000 amperes resistive ac
Terminal Type And Quantity:
8 wire lead
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5930-00-574-2975

Sensitive Switch - Page 2 of 2



Fiig:

A053a0