

View Online at <https://aerobasegroup.com/nsn/5930-00-574-2975>

**Body Style:**

Hole mounted

**Hazardous Locations/environmental Protection:**

Dustproof

**Actuator Style:**

Adjustable arm

**Actuator Height:**

0.937 inches

**Actuator Width:**

0.437 inches

**Housing Height:**

1.250 inches

**Housing Length:**

2.799 inches

**Housing Width:**

1.218 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Height:**

2.588 inches

**Center To Center Distance Between Housing Mounting Facilities Parallel To Length:**

1.875 inches

**Maximum Voltage Rating In Volts:**

250.0 ac and 28.0 dc

**Inclosure Type:**

Fully enclosed

**Nonpile-up Contact Arrangement:**

2 pole, double throw, double break/double make, permanent jumper, one position momentary single switch unit

**Switch Release Force:**

80.0 ounces

**Switch Actuating Force:**

144.0 ounces

**Actuator Movement:**

Between 4.0 pretravel degrees and 8.0 overtravel degrees and 1.5 differential degrees

**Contact Load Current Rating At Maximum Rated Voltage:**

5.000 amperes resistive dc and 5.000 amperes inductive dc and 10.000 amperes resistive ac

**Terminal Type And Quantity:**

8 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A053a0