# NSN 5930-00-574-3640

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-574-3640

## **Thread Class:**

2b single mounting facility

## **Overall Length:**

3.376 inches

# **Overall Height:**

2.188 inches

## **Overall Width:**

2.188 inches

#### First Flat Length:

0.500 inches single actuator

#### Flat Height:

0.218 inches single actuator

### Shaft Diameter:

0.249 inches single actuator

#### Shaft Length:

0.938 inches single actuator

# Individual Section Quantity:

2

# Longest Horizontal Distance Between Mounting Centers:

1.500 inches single mounting facility

# Switch Contact Basic Design:

Nonpile-up symmetrical

#### **Pole Quantity:**

8 each section rear

#### **Throw Quantity:**

3 each section rear

#### **Mounting Method:**

Threaded hole single mounting facility

# Thready Qty Per Inch (tpi):

32 single mounting facility

#### **Thread Size:**

0.164 inches single mounting facility

#### **Contact Voltage Rating In Volts:**

120.0 ac at sea level

# **Mounting Facility Pattern:**

Two position in-line single mounting facility

# Switch Actuator Indexing Position Quantity:

3 single actuator

# Shaft Type:

Round, flatted single actuator

#### **Terminal Type:**

Turret

# NSN 5930-00-574-3640

Rotary Switch - Page 2 of 2



**Contact Switching Action:** 

Makes before breaks, breaks before makes 2nd section rear

## Switch Actuator Positioning Increment:

30.0 degrees single actuator

# Switch Actuator Stop Device Type:

Fixed stop single actuator

# **Contact Load Current Rating:**

15.0 amperes resistive load ac at sea level

# Style Designator:

Tap, square frame

## Thread Series Designator:

Unc single mounting facility

Shelf Life:

N/a

## Unit Of Measure:

--

# Demilitarization:

No

# Fiig:

A052b0