# NSN 5930-00-575-9063

Push Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-575-9063

## Body Style:

Panel mount

#### Hazardous Locations/environmental Protection:

Fungus resistant and salt spray resistant and vibration resistant and shock resistant

#### **Overall Length:**

1.200 inches

#### **Overall Height:**

4.270 inches

#### **Overall Width:**

0.960 inches

#### **Body Length:**

1.183 inches

#### Body Width:

0.800 inches

#### **Body Height:**

4.270 inches

# Actuator Length:

0.970 inches

#### Actuator Style:

Rectangular

# Actuator Width:

0.690 inches

# Actuator Color:

White single actuator and white single actuator

# Illuminated Actuator Color:

Amber single actuator and green single actuator

# Actuator Inscription:

60 mile range single actuator

# Illuminated Actuator Color Sequence:

Upper left green upper right amber lower left amber lower right green

# Maximum Voltage Rating In Volts:

125.0 ac and 28.0 dc

#### Inclosure Type:

Fully enclosed

# Mounting Method:

Panel

# Features Provided:

Holding solenoid

# Nonpile-up Contact Arrangement:

4 pole, double throw, one position momentary single switch unit

# Contact Load Current Rating At Maximum Rated Voltage:

4.000 amperes resistive dc and 2.500 amperes inductive dc and 5.000 amperes resistive ac and 5.000 amperes inductive ac

# NSN 5930-00-575-9063

Push Switch - Page 2 of 2



# Terminal Type And Quantity:

12 turret and 5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A053a0