

View Online at <https://aerobasegroup.com/nsn/5930-00-575-9544>

Thread Class:

3a single pressure connection

Thread Direction:

Right-hand single pressure connection

Overall Length:

3.550 inches

Outside Diameter:

0.438 inches single connection

Body Length:

3.000 inches

Overall Diameter:

0.880 inches

Pressure Switch Type:

Gage

Width Across Flats:

1.000 inches

Mounting Method:

Input port

Contact Action Stimulus:

Increase

Proof Pressure:

4500.00 pounds per square inch gage

Thread Size:

0.4375 inches single pressure connection

Nonpile-up Contact Arrangement:

1 pole, double throw, both positions maintained

Terminal Type:

Connector, receptacle

Contact Load Current Rating:

5.0 amperes resistive load single voltage

Contact Adjustability:

Actuation point not adjustable and deactuation point not adjustable

Contact Stimulus Rating:

1750.00 actuation point pounds per square inch gage and 1500.00 deactuation point pounds per square inch gage

Contact Voltage Rating In Volts:

28.0 dc at sea level single voltage

Pressure Connector Type:

Flared, threaded external single connection

Special Features:

Two lock wire holes

Media For Which Designed:

Liquid

Style Designator:

Cylindrical

Thread Series Designator:

Unf single pressure connection

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A048b0