# NSN 5930-00-575-9834

Rotary Switch - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5930-00-575-9834

**Thread Class:** 2a single mounting facility Thread Length: 0.375 inches single mounting facility **Overall Length:** 3.062 inches **Overall Height:** 1.000 inches **Overall Width:** 0.938 inches **Shaft Diameter:** 0.250 inches single actuator **Shaft Length:** 2.375 inches single actuator **Nonturn Device Radius:** 0.375 inches at 3: 00 o'clock **Individual Section Quantity:** 1 **Nonturn Device Type:** Tab at 3: 00 o'clock **Operating Tempurature Range:** -25.0/+85.0 degrees celsius **Switch Contact Basic Design:** Nonpile-up symmetrical **Pole Quantity:** 2 single section rear **Throw Quantity:** 6 single section rear **Mounting Method:** Threaded bushing single mounting facility **Thread Size:** 0.375 inches single mounting facility **Contact Voltage Rating In Volts:** 28.0 dc at sea level **Switch Actuator Indexing Position Quantity:** 6 single actuator **Shaft Type:** Round, breakoff single actuator **Terminal Type:** Tab, solder lug

**Contact Switching Action:** 

Makes before breaks single section rear

# NSN 5930-00-575-9834

Rotary Switch - Page 2 of 2



## **Switch Actuator Positioning Increment:**

30.0 degrees single actuator

### **Switch Actuator Stop Device Type:**

Fixed-adjustable stops single actuator

### **Contact Load Current Rating:**

500.0 milliamperes resistive load ac at sea level

Style Designator:

Circular wafer, bushing mount

**Thread Series Designator:** 

Unef single mounting facility

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A052b0